

REVISIONS				
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE		

RECOMMENDED
CABLE STRIPPING DIM'S
(建議剝線尺寸)

12.7
4.45

M9XP0.5-6H
FORMING (成形)
FLARE TO $\phi 6.9^{+0.07}$
(撐開至 $\phi 6.9^{+0.07}$)
STAMP (IF ANY)
噴字 (若有要求)
REF. 24
10 SQ.
18.9
11
3.6
2.2

5
6.8

2.4

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- BRASS PER QQ-B-626
- NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- PHOSPHOR BRONZE PER QQ-B-750
- GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- TEFLON MIL-P-19468
- JIS H 3250, C 2600

1. CRIMPED FERRULE
HEX CRIMP SIZE .178"

2. CONTACT PIN TO SOLDER

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
9	NUT			1	15687061606-5
8	INSULATOR	DELIN	NATURAL	1	15687061606-4
7	FERRULE			1	FR-51/445X127
6	CONTACT PIN			1	1561112A1-6-B
5	INSULATOR		NATURAL	1	NS16AAH01A
4	OUTER BODY			1	1561112A1-4
3	BODY			1	1566412A1-2-36/22
2	OUTER CONTACT			1	1561121G1-2
1	SHELL			1	1561121G1-1-B

DIMENSIONS ARE IN MILLIMETERS			
UNLESS OTHERWISE SPECIFIED TOLERANCES			
0.5-6	=	±0.2	
6-30	=	±0.4	
30-120	=	±0.6	
120-315	=	±1	
315-1000	=	±1.6	
1000-2000	=	±2.4	

PART NO.	
APPROVED	DATE
Cheer. 3	03-30-04'
Cheer. W	DATE
03-30-04'	
DRAWN	DATE
LILY	03-30-04'

TITLE	
1.6/5.6 R/A CRIMP PLUG	
DRAWING NO.	
1561112A3-N/3GT3G-BT3002-75	
ITEM NO.	
161112AAE32NF7F	

Amphenol

Danbury,CT,USA-Tainan,Taiwan-Shenzhen,China